

SFP-30 Series



1.25 GIGABIT ETHERNET SFP (SMALL FORM FACTOR PLUG TRANSCEIVER) without SFF-8472 DMI

Features

- Data Rate 1.25 Gbps
- Single +3.3V power supply
- RoHS compliance
- Low power dissipation
- Class I laser product
- Low EMI and excellent ESD protection
- Commercial temperature (0 to 70°C)

Description

Connection Technology Systems SFP (Small Form-factor Plug-in) transceiver Comply with IEEE-802.3z 1000BASE-X standard.

SFP can be mixed and matched on a given switch to maximize flexibility. However, the connection and associated port at the remote end must match the chosen SFP connection type. CTS SFP transceiver can be used in those CTS Switches and Converter which support SFP modules.

Order Information

MODEL	FIBER PORT				
	Speed	Type	Connector	Distance	Wavelength
SFP-30FC	1.25Gbps	MM	LC	550M	850nm
SFP-30FC(SM -10/20/40/50/80/120)	1.25 Gbps	SM	LC	10/20/40/50/80/120KM	1310nm/1310nm/1310nm/1550nm/1550nm/1550nm
SFP-30W2A(SM -10/20/40/80)	1.25Gbps	WDM	LC	10/20/40/80KM	TX:1310nm/1310nm/1310nm/1490nm RX:1550nm/1550nm/1550nm/1570nm
SFP-30W2B(SM -10/20/40/80)	1.25Gbps	WDM	LC	10/20/40/80KM	TX:1550nm/1550nm/1550nm/1570nm RX:1310nm/1310nm/1310nm/1490nm
SFP-30FC-C09	1.25Gbps	CWDM	LC	80KM	1430nm
SFP-30FC-C10	1.25Gbps	CWDM	LC	80KM	1450nm
SFP-30FC-C11	1.25Gbps	CWDM	LC	80KM	1470nm
SFP-30FC-C12	1.25Gbps	CWDM	LC	80KM	1490nm
SFP-30FC-C13	1.25Gbps	CWDM	LC	80KM	1510nm
SFP-30FC-C14	1.25Gbps	CWDM	LC	80KM	1530nm
SFP-30FC-C15	1.25Gbps	CWDM	LC	80KM	1550nm
SFP-30FC-C16	1.25Gbps	CWDM	LC	80KM	1570nm
SFP-30FC-C17	1.25Gbps	CWDM	LC	80KM	1590nm
SFP-30FC-C18	1.25Gbps	CWDM	LC	80KM	1610nm